## KERALA AGRICULTURAL UNIVERSITY

## B.Tech (Food. Engg) 2014 Admission III<sup>rd</sup> Semester Final Examination-January -2016

Cat. No: Meen.2104 Title: Kinematics of Machinery (2+1)			Marks: 50.00 Time: 2 hours
I	Fill	l up the blanks	$(10 \times 1=10)$
	1	. A four bar mechanism hasinstantaneous centers of ro	tation
	2	: The total no: of instantaneous centers of mechanism with n links are	
	3	. Klien's construction is mainly used to determine	
	4	. In belt drives, the centrifugal tensionthe driving power	of belt
	5	. A Hartnell governor is oftype	
	6	. Sensitivity of an isochronous governor is	
	7	. If a governor is too sensitive, it is said to be	
	8	. Helical gears are subjected totype of stresses	•
	9	. The type of cam follower used in aircraft engines isty	ре
	1	0. The maximum magnitude of unbalanced force along the perpendicu	lar to the line o
		stroke is	
II Write short notes on any Five questions			$(5 \times 2=10)$
	1.	Distinguish between initial tension and centrifugal tension in a belt	
	2.	Name the four important systems of gear teeth that are commonly used	
	3.	Explain the term 'train value'? How it is related to velocity ratio	
	4.	Differentiate between centrifugal and inertia governors	
	5.	Differentiate between pivot and collar bearing	
	6.	What do you mean by interference between two mating gears	
	7.	What do you mean by angle of repose	
II	I W	rite short essay on any FIVE questions	$(5 \times 4=20)$
	1.	Derive the condition for constant velocity ration of toothed wheels	•
	2.	Explain general procedure to draw the velocity diagram using one exam	nple
	3.	Explain with sketches different types of cams and followers	
	4.	Define transmission angle of a four bar mechanism	
	5.	What is the significance of contact ratio in gear drive	
	6.	Explain about helical gears and spiral gears	
	7.	Write short note on polynomial cams	

## IV Write essay on any ONE

1. The following data is related to a symmetric circular arc cam operating on a tlat

Least radius of the cam =27.5 mm, total lift =12.5 mm, angle of lift = 55°, nose rad 3mm, speed of the cam = 600 r.p.m, find the following

- a) Distance between cam centre and nose centre
- b) Radius of circular flank
- c) Angle of contact on the circular flank
- 2. In belt drive, the mass of the belt is 1 kg/m length and its speed is 6 m/s. The transmits 9.6 kw of power .Determine the initial tension in the belt and strength of belt. The coefficient of friction is 0.25 and the angle of lap is  $220^{\circ}$